

SCRUTINY LIST

AROCA	AROCA Phillip Island 4 February 2012	Car Number/s	
-------	---	-----------------	--

EXTERIOR			
1	<u>BRAKE LIGHTS</u> – Working & Lenses Clean.		
2	<u>BOOT</u> – Free of Removable Items.		
3	<u>WHEELS</u> – Check Nuts & Ask Entrant to Check Tension.		
4	<u>TYRES</u> – Check Condition, Check for Metal Valve Caps. “R”rated tyres on steel rims are prohibited.		
5	<u>SUSPENSION</u> – Check Ball Joint Wear, Steering Function & Wheel Bearing Tightness.		
6	<u>HEADLIGHTS</u> – Protectors or Taped with Clear Tape.		
7	<u>WINDSCREEN</u> – Check for Clear Visibility (No Cracks) – Ensure both Front & Rear are Clean.		
8	<u>RACE NUMBERS</u> – Displayed per Supp. Regulations.		
9	<u>DOORS</u> – Latches Functioning Properly.		
10	<u>BLUE TRIANGLE</u> – Showing Location of Battery.		
11	<u>TOW HOOKS</u> – with access		

INTERIOR			
1	<u>SEATS</u> – Firmly Secured.		
2	<u>BRAKE PEDAL</u> – Adequate Height and Feel.		
3	<u>SEAT BELT</u> – Secure & In Good Condition.		
4	<u>DOOR LATCHES</u> – Work Properly.		
5	<u>LOOSE OBJECTS</u> – Ensure there are None.		
6	<u>MIRRORS</u> – Secure and Clean (Rear Vision & Wing).		
7	<u>FIRE EXTINGUISHER</u> – To be BOLTED IN, not self tappers. Must Be AS1841.5 & Within Age Limit (See #1 below for complete requirement).		
8	<u>HELMET</u> – Must Be AS1698 & In Good Condition.		
#1	Must Be AS1841.5 . Must be within Reach of Driver and in Metal Bracket securely attached to vehicle. Three Year Limit on age.		

UNDER BONNET			
1	<u>LEAKS</u> – Check for Visible Oil, Water, Petrol & Brake Fluid.		
2	<u>FITMENT</u> – Ensure Petrol Lines, Wires, Hoses & Filters are Securely fitted.		
3	<u>BATTERY</u> – Must Be Secure. If in cabin area, must be secured in battery box.		
4	<u>ACCELERATOR LINKAGE</u> – Ensure No Binding & Secondary Springs are Fitted to Carburetor Vehicles.		
5	<u>BRAKE FLUID</u> – Ensure Level Appropriate.		
6	<u>BONNET FASTENINGS</u> – Secondary Method Required, Except When Forward Hinged (Vehicle After 1/1/1973)		

SIGNATURE OF SCRUTINEER Endorse Log Book (if required)	
--	--